

## **COMPRESSOR POWER 150**

**Air Compressor Oil** 

**COMPRESSOR POWER 150** is a high performance ashless air compressor oil specially designed to meet the stringent requirements of major compressor manufacturers.

**COMPRESSOR POWER 150** is suited for reciprocating air-, rotary screw and vane compressors. Also, used in circulating oil systems, plain and rolling element bearings, lightly loaded gear sets, etc

**COMPRESSOR POWER 150** is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo-oxidative
- Improved equipment reliability, availability and efficiency
- Low ash and carbon forming tendency ensures improved valve performance
- Reduced potential for fires and explosions in the discharge systems
- Exceptional wear and rust
- Superior demulsibility reduces oil carryover and corrosion, maintains lubrication efficiency
- Reduces sludge formation and improves life of coalesces

**COMPRESSOR POWER 150** meets the following performance criteria:

DIN 51506 VBL/VCL/VDL ISO 6521-DAA/DAB/DAG/DAH DIN 51503-1 KAA/KE

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	150
Density @15°C	kg/m3	ASTM D4052	879.0
Kin. Viscosity @100°C	mm2/s	ASTM D7042	15.2
Viscosity Index		ASTM D2270	104
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
Date Issued: 15-5-2025	Supersedes: 02	-06-2022	Revision Nr.: 03

## **Typical Analysis**