

THERM POWER 32

Heat Transfer Fluid

THERM POWER 32 is a premium quality heat transfer oil intended for use in closed indirect heating systems with expansion tanks temperatures up to 315°C.

THERM POWER 32 is based on high quality virgin mineral base oil to ensure the following properties:

- Excellent thermal and oxidation stability
- Minimizes deposit formation and viscosity increase
- Extended service life and reduced downtime
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 315°C with minimal interference with heat transfer capability
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local overheating
- Non corrosive to aluminium, steel, copper, brass or bronze
- Non-toxicity of this oil provides easy disposal of used oil

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Class			32
Density @15°C	kg/m ³	ASTM D4052	875.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	32.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.4
Viscosity Index		ASTM D2270	100
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-12
Date Issued: 15-5-2025		Supersedes: 15-6-2021	Revision Nr.: 02

