

## INDUSTRIAL GEAR POWER 68

### Industrial Gear Oil

**INDUSTRIAL GEAR POWER 68** is a high performance extreme pressure gear oil which is developed for lubrication of heavy duty industrial gears working under severe operating conditions.

**INDUSTRIAL GEAR POWER 68** is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability which helps to resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/moisture.

**INDUSTRIAL GEAR POWER 68** meets the following performance criteria:

DIN 51517-3 CLP

David Brown S1.53.101

AIST 224 (US Steel 224)

ISO 12925-1 CKD

AGMA 9005 E-02

AGMA 9005-F16

JIS K 2219:2006 class 2

### Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	880.3
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	66.8
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	8.7
Viscosity Index		ASTM D2270	102
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
FZG Fail Load Stage, min		DIN 51354-2	12
Demulsibility @54°C	max	DIN 51599	20
Date Issued: 15-5-2025		Supersedes: 10-6-2021	Revision Nr.: 02

