

HANSA SYSPower 3008

Marine system oil

HANSA SYSPower 3008 is a premium quality system oil designed for modern highly rated low speed crosshead marine engines including those employing system oil for piston cooling.

HANSA SYSPower 3008 is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo-oxidative stability.
- Improved detergency keeps crankcase clean.
- Superior water separation characteristics result in trouble free operations.
- Special rust inhibitors protect critical bearing surfaces from rusting.
- Adequate TBN ensures protection against corrosive combustion products.
- Good load bearing capabilities reduce wear in heavily loaded bearings.

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	30
Density @15 °C	kg/m ³	ASTM 4052	890.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	101
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	11.2
Flash Point COC	°C	ASTM D92	>220
Pour Point	°C	ASTM D7346	-15
Total Base Number	mgKOH/g	ASTM D2896	6.7
Sulphated Ash	%Wt	ASTM D874	1.2
Date Issued: 15-5-2025		Supersedes: 15-6-2021	Revision Nr.: 02

