

HANSA POWER DDC 40

2-Stroke Diesel Engine oil

HANSA POWER DDC 40 is premium quality monograde engine oil developed for high output, high speed two-cycle diesel engines. This oil is designed to exceed the performance requirements of API CF/CF-2 and is particularly recommended for Detroit Diesel two-cycle diesel engines in marine fleets operating on low sulphur fuels.

HANSA POWER DDC 40 is based on high quality mineral base stocks in combination with a special selected additive package to achieve the following properties.

- Excellent detergency reduces deposits, sludge build-up & varnish.
- Extend engine life & durability
- Superior thermo-oxidative stability.
- Improved antiwear technology protects against scuffing & wear of cylinder liner and walls
- Special rust inhibitors retard rust & corrosion formation in critical engine parts
- Adequate TBN levels ensure protection against corrosive combustion products

HANSA POWER DDC 40 meets the following performance criteria:

API CF/CF-2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	SAE 40
Density @15 °C	kg/m ³	ASTM 4052	897.1
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	141.4
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.5
Viscosity Index		ASTM D2270	101
Flash Point COC	cP	ASTM D92	210
Pour Point	°C	ASTM D7346	-21
Total Base Number	°C	ASTM D2896	12.1
Sulphated Ash	mgKOH/g	ASTM D874	0.8
Date Issued: 15-5-2025		Supersedes: 15-6-2021	Revision Nr.: 02

