

HANSA MULTI POWER 15W-40

Marine Trunk Piston Engine oil

HANSA MULTI POWER 15W-40 is a premium quality marine engine oil developed to meet the performance requirements of modern turbocharged and naturally aspirated marine diesel engines operating on distillate diesel fuel.

HANSA MULTI POWER 15W-40 is formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

HANSA MULTI POWER 15W-40 meets the following performance criteria:

DTFR 15B110 (MB 228.3)
Mack EO-N
MTU Type 2
Caterpillar ECF-1a
Deutz DQC-III
Cummins CES 20077/20078

Volvo VDS-3
API CI-4/ SL
Caterpillar ECF-2
Global DHD-1
MAN M 3275

Renault RLD-2
ACEA E7
MB 228.1
JASO DH-1
DDC 93K215

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m ³	ASTM 4052	886.3
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	102.0
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	138
Viscosity CCS @ -20 °C, max.	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	11.4
Sulphated Ash	%Wt	ASTM D874	1.5
Date Issued: 15-5-2025		Supersedes: 9-11-2021	Revision Nr.: 04

