

TIDAL POWER SXPD 10W-30

Synthetic MID SAPS Heavy Duty Diesel Engine Oil

TIDAL POWER SXPD 10W-30 is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particulate Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

TIDAL POWER SXPD 10W-30 is formulated with high refined synthetic base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals.
- Complies with strictest European emission regulation.

TIDAL POWER SXPD 10W-30 meets the following performance criteria:

Approved: Volvo VDS-4.5 Mack EOS-4.5 Renault VI RLD-3

DTFR 15C100 (MB 228.31)

Meets: API CK-4 ACEA E7/E8/E11 MAN M3775

DDC93K222 CAT ECF-3 Deutz DQC III-18-LA Cummins CES 20086 MTU Type 3.1 DAF PSQL 2.1 E

DAF PSQL 2.1 E LD DTFR 10C110 (MB 228.51)

SFU: IVECO

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-30
Density @15°C	kg/m³	ASTM 4052	862.6
Kinematic Viscosity @ 40°C	mm²/s	ASTM D704	2 82.6
Kinematic Viscosity @ 100°C	mm²/s	ASTM D704	2 12.2
Viscosity Index		ASTM D227	0 146
Viscosity CCS @ -25°C	сР	ASTM D529	3 5650
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D734	6 -33
Total Base Number	mgKOH/g	ASTM D289	6 10.1
Sulphated Ash	%Wt	ASTM D874	0.9
Date Issued: 14-10-2025	Supersedes: 15-5-2025 Revision		Revision Nr.: 04















