

WAVE POWER PERFORMANCE 5W-40

Semi-Synthetic Passenger Car Motor Oil

WAVE POWER PERFORMANCE 5W-40 is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline engines of passenger car and light vans with or without turbocharger.

WAVE POWER PERFORMANCE 5W-40 is formulated with high quality hydro-treated mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

WAVE POWER PERFORMANCE 5W-40 is suitable for use where the following specifications are required:

API SN/CF

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15 °C	kg/m ³	ASTM 4052	850
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	82.2
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	178
Viscosity CCS @ -30 °C	cP	ASTM D5293	4080
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.4
HTHS 150 °C	mPa.s	ASTM D4683	3.8
Date Issued: 15-5-2025		Supersedes: 11-08-2022	Revision Nr.: 02

