

## RACING POWER 4T 5W-30

### Fully Synthetic 4-Stroke Motorcycle Oil

**RACING POWER 4T 5W-30** is a racing-grade fully synthetic 4-stroke gasoline engine oil. It provides superior cleanliness and protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

**RACING POWER 4T 5W-30** is based on top-quality fully synthetic polyalphaolefin (PAO) and Alkylated Naphthalene base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding thermo-oxidative stability.
- Exceptional anti-wear, anti-rust and anti-corrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature high shear environment.
- Provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures.
- Ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

**RACING POWER 4T 5W-30** meets the following performance criteria:

API SN      JASO MA-2

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	847.8
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	70.7
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	11.5
Viscosity Index		ASTM D2270	157
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D7346	-54
Total Base Number	mgKOH/g	ASTM D2896	9.0
Date Issued: 15-5-2025	Supersedes: 02-12-2022	Revision Nr.: 1	

