

## SPORT POWER 4T 10W-50

### Synthetic 4-Stroke Motorcycle Oil

**SPORT POWER 4T 10W-50** is a premium 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance liquid and air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

**SPORT POWER 4T 10W-50** is based on top quality synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding thermo-oxidative stability.
- Exceptional anti-wear, anti-rust and anti-corrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

**SPORT POWER 4T 10W-50** meets the following performance criteria:

API SN              JASO MA2

### Typical Analysis

| Properties                   | Unit               | Method                 | Typical Value   |
|------------------------------|--------------------|------------------------|-----------------|
| SAE Grade                    |                    | SAE J300               | 10W-50          |
| Density @15 °C               | kg/m <sup>3</sup>  | ASTM 4052              | 859.6           |
| Kinematic Viscosity @ 40 °C  | mm <sup>2</sup> /s | ASTM D7042             | 128.0           |
| Kinematic Viscosity @ 100 °C | mm <sup>2</sup> /s | ASTM D7042             | 18.6            |
| Viscosity Index              |                    | ASTM D2270             | 164             |
| Flash Point COC              | °C                 | ASTM D92               | 201             |
| Pour Point                   | °C                 | ASTM D7346             | -36             |
| Total Base Number            | mgKOH/g            | ASTM D2896             | 8.4             |
| Date Issued: 15-5-2025       |                    | Supersedes: 02-12-2022 | Revision Nr.: 1 |

