

PERFORMANCE POWER 4T 20W-50

Semi Synthetic 4-Stroke Motorcycle Oil

PERFORMANCE POWER 4T 20W-50 is a 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance liquid and air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

PERFORMANCE POWER 4T 20W-50 is based on excellent quality hydrotreated mineral and synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Excellent thermo-oxidative stability.
- Very good anti-wear, anti-rust and anti-corrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Excellent dispersancy and detergency properties.
- Very good shear stability maintains viscosity under high temperature high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

PERFORMANCE POWER 4T 20W-50 meets the following performance criteria:

API SN JASO MA2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m ³	ASTM 4052	869.5
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	147.5
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	18.0
Viscosity Index		ASTM D2270	136
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	9.5
Date Issued: 15-5-2025		Supersedes: 2-12-2022	Revision Nr.: 1

