

RACING POWER 2T

Fully Synthetic 2-Stroke Motorcycle Oil

RACING POWER 2T is a supreme performance synthetic lubricant specially developed for high output air cooled 2-stroke motorcycles and scooters, which are operating under severe conditions.

RACING POWER 2T is based on high quality synthetic (ester) base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional protection against piston scuffing and wear of engine components.
- Exceptional control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Low ash additive technology prevents pre-ignition and spark plug.
- Easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

RACING POWER 2T meets the following performance criteria:

API TC JASO FD ISO-L-EGD

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15 °C	kg/m ³	ASTM D4052	876.6
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	49.1
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	8.7
Viscosity Index		ASTM D2270	158
Flash Point COC	°C	ASTM D92	108
Pour Point	°C	ASTM D7346	-54
Total Base Number	mgKOH/g	ASTM D2896	2.2
Sulphated Ash	%Wt	ASTM D874	0.13
Date Issued: 15-5-2025		Supersedes: 06-07-2023	Revision Nr.: 02

