

PERFORMANCE POWER 2T

2-Stroke Motorcycle Oil

PERFORMANCE POWER 2T is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines deployed in variety of applications.

PERFORMANCE POWER 2T is based on high-quality virgin base oils in combination with a special selected additive package to obtain the following properties:

- Excellent lubricity protects against piston scuffing and premature wear of engine components
- Proven additive technology controls engine and exhaust system deposits
- Low ash formula prevents pre-ignition and spark plug fouling
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.

PERFORMANCE POWER 2T meets the following performance criteria:

API TC JASO FB

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15 °C	kg/m ³	ASTM D4052	879.4
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	71.0
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	9.4
Viscosity Index		ASTM D2270	110
Flash Point COC	°C	ASTM D92	160
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	1.2
Sulphated Ash	%Wt	ASTM D874	0.25
Date Issued: 15-5-2025		Supersedes: 06-07-2023	Revision Nr.: 02

