

## WAVE POWER SPECIAL SFP 5W-30

### Synthetic MID SAPS Passenger Car Engine oil

**WAVE POWER SPECIAL SFP 5W-30** is a high-performance fuel saving MID SAPS engine oil to be used in gasoline- and diesel engines, with and without particle filter, of passenger cars and light vans where a FPW 9.55535/03 specification is required and suitable for all engines which require an ACEA C3 performance specification.

**WAVE POWER SPECIAL SFP 5W-30** is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- High anti-wear performance
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

**WAVE POWER SPECIAL SFP 5W-30** meets the following performance criteria:

Meets	API SP	ACEA C3	Stellantis FPW 9.55535/03
Suitable for	PSA B71 2297	PSA B71 2290	

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	850
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	12.2
Viscosity CCS @ -30 °C	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	215
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	9.9
Date Issued: 25-04-2025	Supersedes: -		Revision Nr.: -

