

WAVE POWER SPECIAL SFP 5W-30

Fully Synthetic Passenger Car Engine oil

WAVE POWER SPECIAL SFP 5W-30 is a very high performance fuel saving engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger cars and light vans. Specially designed to meet the requirements of the Stellantis FPW9.55535/03 specification.

WAVE POWER SPECIAL SFP 5W-30 is formulated with high quality synthetic base stocks in combination with special selected additive technology to achieve the following performance:

- Good thermal and oxidation stability.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Fuel saving properties.
- Excellent detergency and dispersancy properties.

WAVE POWER SPECIAL SFP 5W-30 meets the following performance criteria:

ACEA C3
MB 229.52
MB 226.52
OV 040 1547-G30
GM DEXOS 2

API SQ
MB 229.51
Renault RN17
OV 040 1547-D30
GB 11121

Stellantis FPW9.55535/03
Stellantis FPW9.55535/05
PSA B71 2297
PSA B71 2290

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density @15 °C	kg/m ³	ASTM D4052	851
Kin. Viscosity @40 °C	mm ² /s	ASTM D7042	75.1
Kin. Viscosity @100 °C	mm ² /s	ASTM D7042	12.20
Viscosity Index		ASTM D2270	160
Viscosity CCS @-35 °C	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	9.9
Sulphated Ash	%Wt	ASTM D874	0.75
Date Issued: 14-4-2026		Supersedes: 23-5-2025	Revision Nr.: 1

