

TIDAL POWER SPECIAL FEV 5W-30

Fuel saving MID SAPS Heavy Duty Diesel Engine Oil

TIDAL POWER SPECIAL FEV 5W-30 is a fuel saving MID SAPS, lowered HTHS, super high performance engine oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year.

TIDAL POWER SPECIAL FEV 5W-30 is intended use in specific Euro-6 engines.

TIDAL POWER SPECIAL FEV 5W-30 is formulated on high quality refined synthetic base oil in combination with a special additive package to obtain the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals up to 150.000 km.
- Suitable for engines equipped with a Diesel Particulate Filter (DPF)
- Fuel conserving
-

TIDAL POWER SPECIAL FEV 5W-30 meets the following performance criteria:

Approved:	Volvo VDS 5 DTFR 15C130	Mack EOS-5	Renault VI RLD-5
Meets:	API FA-4 Cummins CES 20087 Ford WSS-M2C214-B1	ACEA F01 JASO DH-2	API SN DDC 93K223

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m³	ASTM 4052	856
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042	54.9
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042	9.8
Viscosity Index		ASTM D2270	167
Viscosity CCS @ -30°C	cP	ASTM D5293	5800
HTHS @ 150°C	mPa·s	ASTM D4683	3.0
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.8
Date Issued: 4-6-2025		Supersedes: 15-5-2025	Revision Nr.: 1

