

ATF POWER F

High-friction automatic transmission fluid

ATF POWER F is a high friction automatic transmission fluid intended for use in automatic transmissions of all Ford vehicles that were built prior to 1977 and certain models built during 1977-1980 requiring fluids meeting Ford ESW-M2C33-F specification.

ATF POWER F is based on special selected highly refined base oil in combination with a special selected additive package to reach to following properties:

- Good thermo-and oxidation stability.
- Frictional characteristics for quick shifts in a variety of driving conditions.
- Improved anti-wear, antirust and anticorrosion technology.
- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Compatibility with all common seal materials.

ATF POWER F meets the following performance criteria:

Ford ESW-M2C33-F Ford ESW-M2C33-G

Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15 °C	kg/m ³	ASTM 4052	867.2
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	38.8
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	7.6
Viscosity Index		ASTM D2270	172
Flash Point COC	°C	ASTM D92	>190
Pour Point	°C	ASTM D7346	-48
Date Issued: 15-5-2025	Supersedes: 17-6-2021	Revision Nr.: 02	

