

PERFORMANCE POWER 4T 25W-60

4-Stroke Motorcycle Oil

PERFORMANCE POWER 4T 25W-60 is a high performance mineral engine oil especially developed for use in air-, oil-, and water-cooled 4-stroke motorcycles to provide excellent protection towards engine, gearbox and wet clutches and ensures the highest possible reliability even under the most severe operation conditions.

PERFORMANCE POWER 4T 25W-60 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Controlled frictional properties eliminate clutch slippage, effectively improving the drivability of the vehicle.

PERFORMANCE POWER 4T 25W-60 meets the following performance criteria:

API SL

JASO MA2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	25W-60
Density @15 °C	kg/m ³	ASTM 4052	896.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	286.8
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	25.9
Viscosity Index		ASTM D2270	117
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
Total Base Number	mgKOH/g	ASTM D2896	7.9
Date Issued: 24-12-2025	Supersedes: -		Revision Nr.: 0

