

SNOWMOBILE POWER PLUS 2T

Fully Synthetic 2-Stroke Snowmobile Oil

SNOWMOBILE POWER PLUS 2T is a supreme performance synthetic lubricant specially developed for high output air and liquid cooled 2-stroke snowmobiles, which are operating under severe conditions. SNOWMOBILE POWER PLUS 2T is specially designed to meet the high performance demands of the BRP E-Tec engines. SNOWMOBILE POWER PLUS 2T is also suitable for all 2-Stroke chainsaw engines.

SNOWMOBILE POWER PLUS 2T is based on high quality fully synthetic (ester) base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional protection against piston scuffing and wear of engine components.
- Exceptional control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Low ash additive technology prevents pre-ignition and spark plug.
- Easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

SNOWMOBILE POWER PLUS 2T meets the following performance criteria:

API TC JASO FD ISO-LEGD TISI Rotax (253) Husqvarna (272)

Suitable for: E-Tec

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15 °C	kg/m ³	ASTM D4052	868.8
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	36.53
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	7.54
Viscosity Index		ASTM D2270	178
Flash Point COC	°C	ASTM D92	>150
Pour Point	°C	ASTM D7346	-48
Total Base Number	mgKOH/g	ASTM D2896	1.9
Sulphated Ash	%Wt	ASTM D874	0.14
Date Issued: 31-03-2026		Supersedes: -	Revision Nr.: -

